


**Artikuls: ELT-WWL/8004RGB-78W**

**Apraksts:** LED gaismas ķermenis, izkliedētas gaismas efekta saņemšanai, tiešais pieslēgums AC 220V, krāsas vadības standarts: RGB 512, augstās intensitātes III paaudzes LED 3-in1 dod iespēju panākt 16 milj. krāsu toņus. IP65 - uzstādīšanai āra apstākļos, optimālais temperatūras režīms: -25° C~ 40° C grādi.

Spriegums:	AC90V~AC260V(50/60Hz)
Jauda:	78 Watts
Gaismas avots:	RGB High Power LED 3-in-1, 350mA DC
Gaismas atdeve:	760lm
RGB signāla standarts:	DMX512
Izmēri:	143x81x988 mm
Darbības temperatūras režīms:	-25 ° C~ 40 ° C
Aizsardzības pakāpe IP:	IP 65
PF:	0,98
Vadības tips:	Master
Korpusa materials:	anodētais alumīnijs
Optika:	alumīnija reflektors 60 grādi, stikls
Svars:	4,5 kg
Garantijas termiņš:	2 gadi
Gaismas avota resurss:	30.000 stundas
Efektivitāte:	30.000 stundas L70 F50



Pieslēgums:

220V input port  
 220V output port  
 Standard DMX 512 signals input port  
 Standard DMX 512 signals output port

Each RGB wall washer has 14 color modes for options.  
 Button 1 is for increasing, and button 2 is for decreasing.

Interface display functions Instructions:

001~512 : means the wall washer is on the mode of being controlled, in this mode, the wall washer will be controlled by the main wall washer.

H-1~H-D: main control mode, in this mode, all the following connected wall washer, can change the same lighting effect as the first one.

Control Way Outside using DMX Control Box or DMX512 Standard Console; Master-Slave Services

